

*Application*  
*for*  
*United States Patent*

*To all whom it may concern:*

Be it known that we, Robert A. Gentala, John DiDomenico, and Craig S. Rendahl,  
have invented certain new and useful improvements in

***OPTICAL PATH STRUCTURE FOR OPEN PATH EMISSIONS SENSING  
WITH SPINNING FILTER WHEEL***

of which the following is a full, clear and exact description:

## OPTICAL PATH STRUCTURE FOR OPEN PATH EMISSIONS SENSING WITH SPINNING FILTER WHEEL

### PRIORITY

[0001] The present application is a continuation-in-part of pending U.S. patent application no. 09/934,272, filed August 21, 2001, entitled Optical Path Structure for Open Emissions Sensing, the disclosure of which is incorporated herein by reference in its entirety.

### FIELD OF THE INVENTION

[0002] The present invention relates generally to remote sensing systems. More particularly, the present invention relates to an apparatus for transmitting, reflecting, and detecting light in an open path sensing system such as a vehicle emission sensing system, having use in detecting and/or measuring one or more components of the air through which the light passes.

### BACKGROUND OF THE INVENTION

[0003] Current methods of determining whether a vehicle is compliant with emission standards include open path and closed path emissions measurement systems. In a closed path system, an emission sensor is directly connected to the exhaust of the vehicle, such as by insertion into a tailpipe. An open path vehicular emissions measurement system collects data by a means other than a direct connection to the tailpipe, such as a remote sensor that analyzes the individual components of emissions. Open path vehicle emission systems are often preferable to closed path systems because they can be used in numerous locations and do not require the vehicle to stop for testing.

[0004] Various open path emission sensing systems have been known. One such device uses a radiation source on one side of a roadway that projects a beam across the roadway to be received by a detector. The radiation source and the detector are located on opposite sides of the roadway. The radiation source emits light spectra that may be used to detect an emission signature by way of absorption of light, or which alternatively may be used to excite emission components so as to cause the components to emit light. The detected emission signature can then be used in various applications, such as the measurement of a vehicle's compliance with emission limits and the determination of the type of fuel that a vehicle is using.

[0005] A disadvantage of many known arrangements is that the radiation sources and detectors must be placed on opposite sides of the roadway from each other. Since both the detectors and radiation sources require power to operate, this means that a separate power supply must be provided on each side of the roadway.

[0006] Some known arrangements have tried to overcome this problem by using a radiation source on one side of a roadway and a reflective apparatus located on the other side of the roadway.

[0007] Accordingly, it is desirable to provide an improved optical transmission, reflection, and detection system as herein disclosed.

SUMMARY OF THE INVENTION

[0008] It is therefore a feature and advantage of the present invention to provide an improved optical transmission, reflection and detection system. In accordance with one embodiment of the present invention, a gas component analysis system includes a first light source capable of emitting a first beam of light having known emission intensities corresponding to one or more of infrared, visible, and ultraviolet spectra. The system also includes a reflection unit, a detection unit capable of receiving the beam and measuring received intensities corresponding to the plurality of light spectra, and a processor capable of comparing the received intensities and identifying a concentration of a component corresponding to the intensities.

[0009] Preferably, the system also includes a first reflector positioned to receive the beam from the first light source and reflect the beam toward the reflection unit. The reflection unit is positioned to receive the beam from the reflector and reflect the beam. Also preferably, a second reflector is positioned to direct the beam reflected by the reflection unit so that the beam may be received by the detection unit. Each reflector preferably comprises an off-axis paraboloidal mirror.

[0010] Also preferably, the system also includes a filter wheel positioned to spin about an axis and receive the beam from the first light source and pass the beam to the reflection unit in pulses. The filter wheel preferably includes a plurality of filters, each of which substantially limits the passage of light to a predetermined spectral wavelength or range of wavelengths.

[0011] Also preferably, the first beam of light travels along an optical path to the reflection unit. In this embodiment, the system also includes a second light source capable of emitting a second beam of light having known emission intensities corresponding to one or more of infrared, visible, and ultraviolet spectra, as well as a beam splitter/combiner positioned to direct the second beam of light along substantially the same optical path to the reflection unit.

[0012] In an alternate embodiment, the system also includes a spinning reflector positioned to spin about an axis and receive the beam from the reflection unit and direct infrared components of the beam to the detection unit in pulses.

[0013] In accordance with another embodiment, a method of measuring concentrations of one or more components of a gas includes the steps of: (1) emitting at least one beam of light having known emission intensities corresponding to a plurality of infrared, visible, and ultraviolet spectra through the gas; (2) using a reflection unit to reflect the beam; (3) using a detection unit to receive the beam; (4) measuring received intensities in the beam corresponding to the plurality of light spectra; and (5) identifying a concentration of at least one component of the gas corresponding to a ratio of the emission intensities and the received intensities.

[0014] Preferably, the method embodiment also includes, either before or after the reflecting step, filtering the beam and passing the beam to the reflection unit in pulses. It may also include, before the detecting step, directing infrared, visible and ultraviolet components of the beam to different detectors and/or spectrometers in the detection unit. Also preferably, in the method embodiment identifying step is performed by a processing

device that is programmed to perform the calculation of a component concentration using a formula corresponding to the Beer-Lambert law.

[0015] In another embodiment, the invention provides, an optical system for a gas component analysis. The system has a first emitter for emitting a first light beam having a first spectrum; a second emitter for emitting a second light beam at a second spectrum; a first receiver for receiving the first light beam; and a second receiver for receiving the second light beam. The first light beam travels along a first path in a first direction and the second light beam travels along a second path in a second direction and at least a portion of the first light path overlaps with at least a portion of the second light path to form an overlapping beam, and at the overlapping beam the first direction is opposite to the second direction.

[0016] In another aspect, the invention provides an optical system for a gas component analysis, that has a first emitter located on a first side of a vehicle path for emitting a first light beam having a first spectrum across the vehicle path, a first receiver for receiving the first light beam, and a spinning filter wheel that filters the beam from the first emitter before the beam crosses the vehicle path.

[0017] In another aspect, the invention provides an optical system for a gas component analysis has a first emitter located on a first side of a vehicle path for emitting a first light beam having a first spectrum across the vehicle path, a first receiver for receiving the first light beam, a plurality of filter elements, and a spinning mirror face that reflects the beam so that the beam reaches each of the filter elements in sequence.

[0018] There have thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated.

There are, of course, additional features of the invention that will be described below and which will form the subject matter of the claims appended hereto.

[0019] In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein, as well as the abstract, are for the purpose of description and should not be regarded as limiting.

[0020] As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0021] FIG. 1 illustrates a preferred embodiment of a source unit of the present invention including housing with window, light sources, filter wheel, beam splitter/combiner, and reflector.

[0022] FIG. 2 illustrates a preferred embodiment of a reflection unit of the present invention.

[0023] FIG. 3 illustrates a preferred embodiment of a detection unit of the present invention including housing with window, reflector, beam splitter/combiner, detector and spectrometers.

[0024] FIG. 4 illustrates an exemplary filter wheel that may be used in accordance with one embodiment of the present invention.

[0025] FIG. 5 illustrates an alternate embodiment of a detection unit of the present invention including housing with window, reflector, beam splitter/combiners, spectrometers, spinning reflector, monolithic ellipsoidal mirror, filter array with gas cells, focusing reflector, and a single infrared detector.

[0026] FIG. 6 illustrates several elements of an exemplary computer of a type suitable for carrying out certain functions of the present invention.

[0027] FIG. 7 illustrates a detection unit using multiple spectrometers and a single detector.

[0028] FIG. 8 illustrates the properties of an ellipsoidal reflector.

[0029] FIG. 9 is a conceptual diagram of some basic components of the present invention, including light source, reflection unit, detection unit, and processor.

[0030] FIG. 10 illustrates the addition of reflectors to the components of FIG. 9.

[0031] FIG. 11 illustrates the properties of a paraboloidal reflector.

[0032] FIG. 12 further illustrates the properties of a paraboloidal reflector.



[0033] FIG. 13 illustrates the addition of multiple light sources with beam splitter/combiners to the components of FIG. 10.

[0034] FIG. 14 illustrates a modification of the embodiment shown in FIG. 13 illustrating the arrangement of opposed sources.

### DETAILED DESCRIPTION OF PREFERRED

### EMBODIMENTS OF THE INVENTION

[0035] A preferred embodiment of the present invention provides an improved optical source, reflection, and detection system for gas component analysis. A preferred embodiment includes a light source unit, which preferably includes one or more of infrared, visible, and ultraviolet light sources; a reflection unit; and a light detection unit. Preferably, light sources and detectors are contained within a housing. The light is transmitted through a gas, such as air containing vehicle emissions, reflected, and detected for analysis and measurement of the amount of absorption that has occurred at known wavelengths of the light. The amount of absorption may be used to determine concentrations of gases corresponding to the specific wavelengths.

[0036] In a preferred embodiment of this invention, infrared, visible, and ultraviolet radiation is combined into one beam, directed across a path such as a road along which vehicles travel and generate exhaust, reflected back across the path, collected and concentrated, separated again, and received by one or more discrete detectors and/or spectrometers. In order to be able to separately analyze each range of wavelengths, the infrared light passes through a sequence of filters and/or gas cells either before or after traversing the path of light across the road. The filters are preferably narrow band pass filters

and the gas cells contain known concentrations of gases of interest, such that each filter or combination of filters and gas cells is specific to a gas of interest. In one embodiment, a spinning wheel holds the filters and passes each filter in front of the infrared light source in sequence, before the light traverses the road. In an alternate embodiment, the infrared light, after traversing the road, is distributed by a spinning reflector, such as a mirror, into a stationary array of filters and/or gas cells in sequence to an ellipsoidal mirror or an array of ellipsoidal mirrors that focus the light into a single detector. The visible and ultraviolet light is directed to one or more spectrometers that can analyze the desired wavelength ranges directly.

[0037] A portion of a preferred embodiment of the present inventive apparatus is illustrated in FIG. 1. FIG. 1 illustrates a possible light source component of the present invention. The light source component shown includes an infrared light source 10, a source of visible light 11, and an ultraviolet light source 12. The infrared light 14 emitted by the infrared source 10 passes through a filter wheel 16, more completely described in FIG. 4. Then it is reflected by a beam splitter/combiner 18, and follows an optical path 20 until it reaches a reflector 26 such as an off-axis paraboloidal mirror or spherical mirror. An off-axis paraboloidal mirror is preferred over a spherical mirror due to the aberrations in light that occur with spherical mirrors, however production economics may dictate the use of spherical mirrors. The reflector 26 reflects the infrared light along a path 22, through a protective window 25 in the housing 27, leading to a reflection unit illustrated in FIG. 2.

[0038] The reflector 26 and other optical components described in this embodiment are protected by a window 25 that allows the transmission of all of the wavelengths of interest. This window 25 is attached to the housing 27 of the entire source unit. Preferably, the light sources and detectors are included within a single housing. However, the light

sources and the light detectors may optionally be provided in more than one housing. Also preferably, the housings are sealed to prevent contaminants such as soot, road dust, and other road debris from damaging or coating the internal components and thus degrading the light signal received and/or transmitted by them. Also preferably, the sealed housings contain windows to allow light of the wavelengths of interest to leave and enter the housings as required for the light to travel along the desired optical path. These windows are preferably made of a material such as calcium fluoride ( $\text{CaF}_2$ ), sapphire, or other material that will pass light of all wavelengths of interest with little or no attenuation. Optionally, the windows may be coated by a particular type of coating such as an anti-reflection coating or other suitable coating to enhance the transmission of light of the wavelengths of interest.

[0039] The infrared light source 10 may be any source that emits a sufficient intensity of light of the wavelengths of interest. The reflectors and optical path length determine the size of the spot from the infrared source that contributes to the light beam. Preferably the source is chosen, such that the light emitting area of the filament is as close to that spot size as possible for minimum power consumption.

[0040] Preferably, the filter wheel 16 is a spinning wheel that is powered by a motor 15 that spins the wheel 16 about an axis 19. Also preferably, a synchronization device 58 is provided to track the position and rotational speed of the filter wheel 16. Features of the filter wheel 16 are more completely illustrated in FIG. 4.

[0041] In addition, visible light from source 11 is focused by an optical element 13 to bring diverging light rays back into a focus through the center of ultraviolet source 12 where it is combined with the ultraviolet light from source 12 into a combined beam 24. The combined visible and ultraviolet light 24 passes through the beam splitter/combiner 18 such

that it also follows optical path 20 to the reflector 26, where the light is reflected to also follow path 22 out window 25 toward the reflection unit illustrated in FIG. 2. The visible light source 11 may be a light emitting diode (LED), which emits light in a narrow range of wavelengths, or another visible source such as a halogen lamp that emits a broader range of wavelengths. The advantage of passing the visible light through the ultraviolet light source is eliminating the need for another beam splitter/combiner, saving optical power that would otherwise be lost by the inefficiency of the beam splitter/combiner, in addition to saving space within the enclosure 27. However, if it is desirable to have an ultraviolet source 12 of a design that does not allow for pass-through of the visible light, then alternatively, the visible source 11, and ultraviolet source 12 may be reconfigured to take, for example, positions 146 and 144 as illustrated in an arrangement of sources in FIG. 13 that will be discussed further below.

[0042] The visible light source 11 is an option and is not required for gaseous measurements. However, such a source allows the performance of additional tests on detected light associated with visible spectra, such as an opacity test. One type of opacity test that may be performed is the Society of Automotive Engineers J1667 opacity test, also known as the "Snap Acceleration Test", which measures concentrations of light spectra in the range of 562 through 568 nanometers. Preferably, the visible source 11 can be sufficiently broad in its output wavelength characteristics to also permit detection of blue smoke, which may be indicative of a vehicle that is burning excessive lubricating oil, and particulate matter of varying sizes. Alternatively, more than one visible source optimized for specific causes of exhaust opacity may be used.

[0043] The ultraviolet light source 12 is preferably an ultraviolet lamp such as deuterium lamp, a xenon lamp, or another lamp that has ultraviolet light emission characteristics broad enough to include wavelengths of interest.

[0044] As FIG. 1 illustrates, where multiple light sources such as components 10, 11, and 12 are provided, the emitted beams preferably follow substantially the same optical path 20 toward the reflector 26. The reflector 26 is positioned such that light sources 10, 11, and 12 are near the focal point of the reflector 26 and the reflected light 22 is parallel to its axis of rotation. The angle between the incoming 20 and reflected light 22 and the focal length are determined by the design of the reflector 26 and may be chosen based on considerations of component layout and F-number. (F-number of an off-axis paraboloidal mirror is defined as the diameter of the mirror divided by its effective focal length.) Thus, light 20 transmitted to the reflector 26 is reflected in a direction 22 that is away from the original light sources 10, 11, and 12. In addition, if beam splitter/combiner 18 is a neutral density filter, it is preferably chosen so that the proportion of visible and ultraviolet light passed and the proportion of infrared light reflected are balanced according to the requirements of the detection unit. Optionally, a beam splitter/combiner 18 that is sensitive to different wavelengths such as a dichroic beam splitter may be used instead of a neutral density filter for beam splitter/combiner 18. In order to use some types of beam splitter/combiners, the positions of the infrared 10 and visible/ultraviolet sources 11, 12 may be reversed.

[0045] Optionally, only the infrared light source 10, and not the visible or ultraviolet sources 11, 12, may be provided. In such an embodiment, the beam splitter/combiner 18 may also optionally be omitted, with the infrared light source 10, filter wheel 16, and associated components, taking the position of the ultraviolet source 12 in such an alternative arrangement. This option of the preferred embodiment may be desired for more economical

utilizations of this embodiment where not all exhaust emissions constituents are desired to be measured, or a preference exists to simplify the production of such an embodiment with the potential compromise of poorer data quality.

[0046] FIG. 2 illustrates an exemplary reflection unit, which in an embodiment used to detect vehicle emissions is preferably placed across the road from the light source and detector components, creating an open-path emissions testing system. The reflection unit includes a retro-reflective system, preferably a vertical system, and preferably comprising three mirrors positioned to form 90° angles with respect to each other. A vertical orientation of the mirror assembly is preferred in order to adequately capture the emissions of vehicles of all profiles and heights. Referring to FIG. 2, incoming light 22 is reflected by a first mirror 30 and a second mirror 32. The first and second mirrors are adjacent or substantially adjacent to each other to form a 90° angle. The light reflected by the first and second mirrors is transmitted to a third mirror 34. As FIG. 2 illustrates, the flat reflective portion of third mirror 34 forms a 90° angle with the flat reflective portions of both first mirror 30 and second mirror 32. It is not important to have mirrors 30,32 on top of mirror 34, as this orientation could be reversed without any change to the quality of reflection of light. Light 36 that is reflected by third mirror 34 is then transmitted to the detection unit and travels in a direction that is parallel to the incoming light 22 in a configuration as illustrated in FIG. 9 to be discussed later in this text. The incoming light 22 and/or the reflected light 36 pass through an air component that is to be measured, such as vehicle emissions.

[0047] FIG. 3 illustrates an exemplary detection unit that receives the light that is generated by the source component of FIG. 1, and reflected by the reflection unit of FIG. 2. Referring to FIG. 3, incoming light 36 passes through a protective window 35 that has similar characteristics to the window of the source unit illustrated in FIG. 1, is reflected by a reflector

38 such as an off-axis paraboloidal mirror or spherical mirror that reflects light along an optical path 40 at an angle relative to the incoming light 36. The light transmitted along the optical path 40 is reflected by a beam splitter/combiner 44 that directs infrared light 48 toward infrared detector 50. Preferably, the infrared detector 50 is positioned within the focal volume so that the light will over-bathe the detector's active area to allow for system vibration without adversely affecting measurements by causing a portion of the detector's active surface to temporarily not have light exposure in a vibration occurrence. Focal volume is defined as the three-dimensional volume of light, in which the light is focused to its maximum intensity, in this instance infrared light 48, that travels to the detector 50. Maximum intensity of light occurs when all light's rays are concentrated into the smallest cross-sectional area of the focal volume. This cross-sectional area is not necessarily located at the focal point of the reflector 38, but is located farther away from the reflector 38 than the focal point.

[0048] Small, economical, durable, and versatile spectrometers 42, 43 are commercially available for most ranges of wavelengths of interest in the visible and ultraviolet regions. In the infrared region, however, spectrometers are less practical than individual detectors optimized for particular ranges of wavelengths. These infrared detectors are expensive and require cooling and complicated electronics for support. It is therefore a great advantage to use only a single infrared detector 50 in the detection unit. If separate detectors are used to detect the intensity of each wavelength or band of wavelengths of interest, the calibration problem caused by the different sensitivities of the different detectors must be addressed. This problem is further compounded because sensitivities change with time and temperature and can be different for each detector. Therefore a system using only a single infrared detector 50 is much simpler and is preferred.

[0049] The infrared detector 50 is preferably composed of mercury-cadmium-telluride (MCT), preferably utilizing at least three-stage thermal electric cooling. However, a lead-selenide or other composition detector can be used, and with greater or lesser staged cooling. A liquid cooled detector could also be utilized in this embodiment provided there is supporting equipment to accommodate the liquid cooling. Another possibility for cooling the detector is by Stirling Engine cooling, however this adds cost and complexity. The MCT composition detectors offer a more compatible electronic biasing consistent with reduced noise than other composition detectors. Other factors considered for single detector selection is the detectivity, commonly expressed in terms of "D\*", responsivity to light, the timing of the pulses of light to which the detector is exposed, and the saturation level.

[0050] This embodiment also prefers the economy of a photoconductive type of single detector as opposed to the more expensive photovoltaic detector. While photovoltaic detectors comparably offer less noise in lower pulse frequencies, this is not an issue for this embodiment as it is desirable to stimulate the detector with as high a frequency that the spinning filter wheel illustrated in FIG. 1 item 16, or spinning reflector illustrated in FIG. 5 item 62 will allow.

[0051] Lastly, a detector needs to be selected to respond to light consistent with the range of desired wavelengths. A range of mid-infrared wavelengths for this embodiment can be viewed in **Table 1** which suggests a detector sensitivity range of wavelengths between roughly 3-5 microns. However, if alternative wavelengths are used for such embodiment to measure the gases of interest, the desired range of wavelengths to which the detector is sensitive may have to be adjusted.



[0052] If the range of infrared wavelengths of interest is too broad for a standard detector, a dual substrate detector may be used. A commercially available dual substrate detector contains two different semiconductor compounds, each sensitive to slightly different ranges of wavelengths. They are mounted in a single detector package, one in front of the other so that their active areas nearly coincide. Thus the combination performs as if it were a single detector with sensitivity to a broader range of wavelengths than would otherwise be possible.

[0053] The beam splitter/combiner 44 may comprise any reflective or transmissive device, such as a neutral density filter, which transmit a specified fraction of the incident light and reflect almost all of the rest, treating a broad range of wavelengths equally, or dichroic beam splitter/combiner that can be designed to reflect almost all of the incident light of a specific range of wavelengths, and transmit almost all of the rest. The beam splitter/combiner 44 passes all or portions of visible and/or ultraviolet light 46 so that the visible and ultraviolet spectra may be measured by one or more spectrometers 42, 43. The light which passes through beam splitter/combiner 44 is split off and carried to the respective spectrometers in one of two ways. The first, illustrated in FIG 3, is to focus light onto the end of a Y-shaped optical fiber cable 41 that first receives the light in a single open end of the fiber optic cable, then divides the light within the cable sending a portion of the light to each spectrometer.

[0054] An alternative method of splitting the light to two or more spectrometers, illustrated in FIG. 7, is to use separate beam splitter/combiners 44 and 162 to split light beam 40 twice. Beam splitter/combiner 44 first splits beam 40 into beams 170 and 172. Beam 170 is focused directly into the opening of spectrometer 43 while beam 172 continues on to beam splitter/combiner 162. Beam splitter/combiner 162 then splits beam 172 into beams 174 and 176. Beam 174 is focused on spectrometer 42 while beam 176 continues on to be focused on

the infrared detector 50. In either embodiment, whether cable splitting of light as illustrated in FIG. 3 or multi-beam splitting method of FIG. 11, the light slightly over-bathes the opening to the optical fiber cable (FIG. 3 item 41) or the light orifice of the spectrometer 42,43 for resistance to vibration and coincident reduction of light intensity with the vibration for similar reasons as expressed above for the infrared detector 50.

**Table 1: List of Some Example Tailpipe Emissions Channels and their Wavelengths**

<u>Component</u>	<u>Wavelength</u>
Carbon Monoxide (CO)	4.65 $\mu$
Carbon Dioxide (CO <sub>2</sub> )	4.30 $\mu$
HC <sub>1</sub> (Alkane series hydrocarbons)	3.45 $\mu$
Methane (CH <sub>4</sub> )	3.31 $\mu$
HC <sub>2</sub> (Alkene series hydrocarbons)	3.17 $\mu$
HC <sub>3</sub> (Alkyne series hydrocarbons)	3.01 $\mu$
H <sub>2</sub> O <sub>(v)</sub>	2.90 $\mu$
Nitrogen Monoxide (NO)	0.226 $\mu$
1,3 Butadiene (C <sub>4</sub> H <sub>6</sub> )	0.210 $\mu$
Ammonia (NH <sub>3</sub> )	0.208 $\mu$
Reference	3.90 $\mu$

[0055] In a preferred embodiment, the transmission and detection of light at the wavelengths of mid-infrared listed in Table 1 is accomplished by using a spinning filter wheel as the filter component (referred to in FIG. 1 as item 16). FIG. 4 illustrates an exemplary spinning filter wheel. Referring to FIG. 4, the spinning filter wheel contains light filters such as 52 that correspond to wavelengths associated with individual emission components, such as those illustrated in Table 1. One of the filters 54 must correspond with a wavelength at which no gaseous absorption takes place. Such a filter is known as a “reference” filter 54. The light intensity measured from the reference filter 54 is used to normalize the light intensity measured from each of the gaseous filters 52, so that concentrations of those gases may be calculated by a processor (FIG. 6 item 92). FIG. 4 illustrates a wheel having eight filters 52, 54 each utilizing one of the mid-infrared wavelengths of Table 1, however fewer and/or additional filters, corresponding to fewer and/or additional vehicular exhaust constituents, may be used in alternate embodiments. Each filter 52 is designed to allow light of a specific range of wavelengths to pass through it.

[0056] Another innovation regarding the filters 52,54 is that they are quadrants of an industry standard 25 millimeter optical filter. The round, 25 millimeter diameter filters are cut into four pie shapes allowing for filters to cost one-fourth of what they would otherwise cost if an entire industry standard sized filter were to be inserted in each of the open positions on the filter wheel 16. In addition to cost, there is a savings in the amount of rotating mass by quartering the industry standard sized filters that the wheel 16 would have if the filters were installed whole. Lastly, special slots exist in the wheel 16 to allow for a two-piece optical filter 52,54, should this be necessary. There are occasions when a filter manufacturer will supply two filters in order to provide the desired band pass of wavelengths to measure a gas of interest. The wheel 16 has the capability to accept these two-piece filters.

[0057] In addition, the filter wheel preferably will have one or more synchronization marks 56 that may be detected by a synchronization unit 58 to define either the exact filter or the start of a sequence of filters that will be in the optical path. The wheel 16 must have an opaque area 60 between each filter. The opaque areas 60 prohibit source light (FIG. 1 item 10) from getting to a detector when the opaque areas 60 pass in front of the infrared source (FIG. 1 item 10) transforming the incident light beam into a sequence of pulses (FIG. 1 item 17). In operation, the wheel spins about an axis 19 at high speeds, preferably at least 12,000 rotations per minute, to form a sequence of infrared light pulses (FIG. 1 item 17). Faster rotational speeds are even more preferable since they increase the sampling rate of the emission medium. The synchronization unit (FIG. 1 item 65) allows the processor (FIG. 6 item 92) to associate a wavelength of interest, and corresponding gas of interest, with each pulse of light seen by the detector (FIG. 6 item 90). This combination overcomes disadvantages of prior art, which require discrete detectors for each wavelength.

[0058] In accordance with an alternate embodiment of the present invention the light source unit illustrated in FIG. 1 may omit the spinning filter wheel assembly 15,16,19,58. In this embodiment, an alternate detector unit is provided as illustrated in FIG. 5. Incoming light 36 transmitted from the source unit of FIG. 1 and reflected by the reflection unit of FIG. 2 passes through window 35 that has similar characteristics to window of source unit illustrated in FIG. 1, and is reflected by a reflector 38, which directs the light beam 40 onto beam splitter/combiners 44,45 which direct portions 46,47 of the light to the spectrometers 43,42. The rest of the light 61 is focused on spinning reflector 62. Reflector 62 is a single faceted flat mirror with a reflective surface that is optimized for the infrared light wavelengths of interest, such as an enhanced gold reflective surface or other suitable reflective surface. Alternatively, a multifaceted spinning mirror may be used, however the geometry of the rest

of the layout would have to be modified from what is illustrated in FIG. 5. The spinning reflector 62 splays the light in sequence around a stationary array of filters 52,53,54 and gas cells 70 by directing the beam 64 into the side of monolithic ellipsoidal mirror 80 which reflects the light 66 into the array, consistent with the splaying of the light. After passing through each stationary band pass filter 52,53,54 and gas cell 70, the light beam 72 is redirected to and focused on a single infrared detector 50 by a reflector 74 such as a spherical mirror. The reflective surfaces of reflectors 80 and 74 are optimized for the wavelengths of interest in the same way as the surface of spinning reflector 62. The single infrared detector sees a sequence of pulses of light 76 that are essentially the same as those illustrated as FIG. 3 item 48. Each filter 52,53,54 of this array substantially limits the passage of light to a predetermined spectral wavelength or range of wavelengths. Some filter center wave specifications are listed in Table 1. Each gas cell 70 of this array substantially limits the passage of light of a particular spectral pattern of wavelengths absorbed by the known concentration of the gas of interest that the cell 70 contains.

[0059] Another advantage of this embodiment is that there is much less rotating mass in the spinning reflector 62 than in the spinning filter wheel illustrated in FIG. 4. Therefore the spinning reflector 62 can be spun at a much faster rate than the spinning filter wheel illustrated in FIG. 4. Faster spin rate corresponds to a higher sampling rate that can contribute to lower electronic and optical noise levels, and provide better time resolution of a plume of vehicle exhaust constituents.

[0060] It is instructive to refer to the illustration of FIG. 8 to further the understanding on why an ellipsoidal mirror (FIG. 5 item 80) is chosen to distribute light. An ellipsoidal mirror 200 has two focal points or foci 206,208. Such mirrors have the property that all light rays 202 diverging from a small spot near one focal point 206 are reflected in such a way that

those rays 210 are again focused into a small spot near the other focal point 208 of the mirror 200. Given the unique layout of the alternative embodiment of FIG. 5, and commensurate need for a dual foci reflective device for light distribution through a full 360° of rotation of the spinning reflector (FIG. 5 item 62), an ellipsoidal mirror is the best choice for this alternative embodiment.

[0061] An alternative embodiment replaces the monolithic ellipsoidal mirror 80 with individual ellipsoidal mirrors and may place the filters 52,53,54 and gas cell 70 array before the individual ellipsoidal mirrors if layout and construction is simplified. This alternative can provide the advantage of the system suffering less light loss through use of individual mirrors as opposed to the monolithic ellipsoidal mirror 80. The disadvantage is that there may be more adjustments required in order to have the system of FIG. 5 properly aligned such that all light through the system is optimized.

[0062] FIG. 6 illustrates several elements of a computer processing device that may be used in accordance with a preferred embodiment of the present invention. Referring to FIG. 6, the detection unit 90 delivers emissions-related data to a processor 92. The detector may be any of the detectors or spectrometers as illustrated in FIGS. 3 and 5, or any device that receives or contains information collected by such detectors or spectrometers. Such detector systems for the purpose of discussion in FIG. 6 include a means for amplifying and converting the detector signals into digital signals that can pass to the processor 92 via a direct link such as a parallel data bus 94.

[0063] In this embodiment, the detection unit 90 is part of the unit that contains the processor 92, and the delivery is performed over a parallel bus 94 such as that which can be found in AT, ATX, EBX, and other motherboard styles upon which computers are based.

However, the processor 92 and detection unit 90 may be separate, such as with the remote detector 96 illustrated in FIG. 6. Where a remote detector is used, the data may be delivered to the processor 92 by a communications link 100 that delivers the data to an input port 98 such as a communications port. A wireless communications link 102 and receiver 105 for such a wireless communication are also illustrated in FIG. 6. The communications link 102 may be a direct wire, an infrared data port (IrDA), a wireless communications link, global communications network such as the internet, or any other communications medium.

[0064] The system illustrated in FIG. 6 also includes a memory 104 which may be a memory device such as a hard drive, random access memory, or read only memory. A portion of this memory 104 can contain the instructions for the processor 92 to carry out the tasks associated with the measurement of vehicular emissions. Preferably, concentrations of gases may be derived using the Beer-Lambert Law, however other tests and formulae may be used in alternate embodiments.

[0065] The Beer-Lambert Law, as disclosed in other art, relates absorbance of light to a concentration of gas where an amount of change in light intensity at a known wavelength is proportional to the concentration of a gas of interest at the wavelength of light where the gas is absorbed. The Beer-Lambert Law is expressed in terms of transmittance in Equation 1.

**Equation 1: Beer-Lambert Law**

$$2 - \text{Log}_{10} (\%T) = \epsilon Cl$$

Where:

$\%T$  is the amount of light transmitted through open air and the emissions sample expressed in percent units;

$\epsilon$  is the absorption coefficient for the gas of interest at a corresponding wavelength of absorption;

$C$  is the concentration of the gas of interest expressed in parts-per-million (ppm)  
 $l$  is the path length expressed in meters.

[0066] Transmittance is further expressed as the amount of light that passes through the gas of interest in proportion to the amount of light that was originally emanated from the light source unit as illustrated in Equation 2.

**Equation 2: Transmittance as Expressed in Percent**

$$\%T = \frac{I_p}{I_o} \times 100$$

Where:

$I_p$  is amount of light left after passing through the gas sample of interest

$I_o$  is the amount of light that was originally sent through the entire sample path and not absorbed by the gas of interest

[0067] The specific application of Beer-Lambert Law for this embodiment is found in Equation 3. Equation 3 is an algebraic substitution of transmittance “%T” (Equation 2), and subsequent manipulation of Beer-Lambert Law Equation 1 to solve for a concentration of a gas in an open path, as this is the unknown for which this embodiment measures.

**Equation 3: Application of Beer-Lambert in this Embodiment**

$$C = \frac{2 - \text{Log}_{10}\left(\frac{I_p}{I_o} \times 100\right)}{\epsilon \times l}$$

[0068] Other memory devices 106 and 108 such as additional hard disk storage, a CD-ROM, CD-RW, DVD, floppy drive, ZIP® drive, compact flash compatible device such as that which conforms to IBM Microdrive™ specification, or other memory device may also be included. An internal memory device 106 can be used to extend the number of emissions



tests that can be conducted and retained by this preferred embodiment. A removable memory device 108 can be used to make the emissions data portable to allow for the emissions data to be further processed in a centralized location. The device also optionally and preferably includes a display 110 and/or a transmitter 112 for providing output to a user or another device.

[0069] Utilizing a computer processor 92, the intensity measured by the detector unit 90 at a wavelength of interest is compared by the processor 92 to the intensity of light detected by the detector unit 90 at a reference wavelength where no absorption of gases occurs. This method of detection is commonly known as Differential Optical Absorption Spectroscopy (DOAS). This DOAS methodology is a simple, inexpensive means of determining a concentration of a gas of interest emanating from a vehicle tailpipe in open air, and has examples in other art and fields of invention.

[0070] Alternatively, again using a computer processor 92, the intensity measured by a detector unit 90 at a desired wavelength for an interval of time, followed by measuring light at the detector unit 90 for an interval of time at the same desired wavelength with additionally a gas cell of known concentration of gas that absorbs light of the same wavelength can also be used as a methodology to determine a concentration of a gas of interest. This method of detection is commonly known as Gas Filter Correlation Radiometry (GFCr), and is documented in other art. GFCr has the potential to provide improved precision & accuracy of measurements due to the fact that the methodology allows for the constant referencing of a measurement to a known concentration of the gas of interest.

[0071] A preferred embodiment of FIG. 5 shows both DOAS and GFCr methods of determining a concentration of a gas of interest contained within the same embodiment. For

example, an optical filter 53 can be optimized for sampling carbon dioxide ( $\text{CO}_2$ ). Another filter 54 can be optimized to pass wavelengths of light where no absorption of  $\text{CO}_2$  or other gases exist; such a filter is used for reference to assess the amount of light that passes through the sample path without  $\text{CO}_2$  influence. As the amount of  $\text{CO}_2$  concentration increases, the amount of light that the detector 50 observes through filter 53 will decrease, while the amount of light that the detector 50 observes through the reference filter 54 will remain unchanged. This is the fundamental of the DOAS methodology by comparing the amount of light ( $I_p$  in Equations 2 and 3) off from the  $\text{CO}_2$  filter 53 to the amount of light ( $I_o$  in Equations 2 and 3) from the reference filter 54. Switching the light paths between the  $\text{CO}_2$  path, created by filter 53 to detector 50, and reference path, created by reference filter 54 to detector 50, is accomplished by the spinning reflector 62 that splays the light for periods of time between the two mentioned paths and other paths that exist in this embodiment.

[0072] DOAS methodology is also provided in the embodiment illustrated in FIG. 1, however the light path switching is performed by the spinning filter wheel 16 such that, for a moment in time, the filter wheel rotation exposes an optical filter (FIG. 4 item 52) to light (FIG. 1 item 10) for a gas of interest, then for a roughly equal interval of time, the filter wheel exposes a reference filter (FIG. 4 item 54) to the same light (FIG. 1 item 10).

[0073] The GFCr methodology is provided in this embodiment as well. Expanding on the DOAS example above, a  $\text{CO}_2$  filter 53 can be paired with another similar characteristic  $\text{CO}_2$  filter 52 with the difference that the  $\text{CO}_2$  filter 52 has a windowed small cell 70 that contains a sample of  $\text{CO}_2$  gas. The amount of gas in the cell 70 is chosen based on the amount of optical depth that is desired with which the non-celled optical path is compared. The  $\text{CO}_2$  filter 53 must have balancing windows 78 of the same optical characteristics as the gas cell 70 in order to make the amount of light between both light paths roughly equivalent.

An alternative embodiment to the balancing windows 78 can use a second gas cell 70 in place of the balancing windows 78, but with all air evacuated to a vacuum, or air replaced with nitrogen or other inert gas at partial pressure to provide the optical balance. If a gas is used to fill the balancing cell, the gas cannot have absorption characteristics similar to the gas of interest being measured.

[0074] The balancing windows 78 are added to create an optical balance for the two CO<sub>2</sub> detection paths in the example given, such that the only difference in intensity of light to the detector 50 between the two paths is a change in concentration of the gas of interest. For a period of time, the light travels through the CO<sub>2</sub> filter 52 with CO<sub>2</sub> gas cell 70 and reaches the detector 50. In another time interval of approximately same length, the light will travel through the other CO<sub>2</sub> filter 53 with balancing windows 78 and on to the detector 50. Since the gas cell 70 contains a known concentration and corresponding optical depth of a sample of CO<sub>2</sub>, the amount of light in the filter 52 to gas cell 70 to detector 50 path of light exists as a reference to which the amount of light from light path filter 53 to balancing windows 78 to detector 50 is compared. The amount of absorbance from each CO<sub>2</sub> light path is compared to determine a concentration of CO<sub>2</sub> in this example. As with the DOAS method of detection, light path switching is accomplished by the spinning reflector 62 that provides light to each mentioned path for a period of time in addition to making light paths for other gas sampling paths of this embodiment.

[0075] The unique advantage of GFCr is that any interferences to measuring a concentration of CO<sub>2</sub> in this example appear in both CO<sub>2</sub> light paths and therefore is commonly rejected among both light paths. Common mode rejection of interferences does not necessarily happen with the DOAS method of detection of gases, because of the use of a reference filter at a different wavelength, an interference could conceivably absorb light at the

reference wavelength but not at the wavelength corresponding to the gas of interest. Also, the characteristics of the reference filter 54 are different from the other filters 52,53, and create a situation where different filters 52,53,54 pass different wavelengths of light, to which the detector 50 will have greater or lesser sensitivity to such wavelengths. With proper optimizations, these effects may be minimized, but not eliminated.

[0076] It should be noted that it is not necessary to have both DOAS and GFCr methodologies utilized in an embodiment in order to obtain reasonable measurements of concentrations of gases of interest. However it is desirable to have both when economically feasible in order to provide for improved precision and accuracy of measurements. Furthermore, although an example was given here for CO<sub>2</sub>, it is possible to utilize GFCr for other gases including but not limited to carbon monoxide (CO), methane (CH<sub>4</sub>), and any gas of interest that can be stored over long periods of time in a gas cell without the reference gas of interest degrading, attacking the walls of the cell and compromising the sample, or the reference gas combining with contaminants within the cell causing the reference concentration to no longer be known. GFCr methodology also is beneficial for speciation of hydrocarbons, as the gas cell 70 can be utilized as a sort of notch filter to indicate a particular gas of interest from a group of gases such as hydrocarbons.

[0077] Referring back to FIG. 6 the processor 92 of the embodiment, coupled with the appropriate instruction set contained within memory 104, can be capable of conducting either DOAS, GFCr, or simultaneously both methodologies of detection of concentrations of gases and then applying the concentrations to a combustion equation. Previous art in this field of invention has documented combustion equations that utilize ratioing concentrations of gases of interest relative to carbon dioxide (CO<sub>2</sub>) to correct for any dilution effects in the exhaust stream of the vehicle being tested. The memory 104 can contain combustion equations

unique to different fuels used to power vehicles that are tested by this preferred embodiment. Determination of the type of fuel used to power a tested vehicle can be done in the processor 92 at the time of measurement of the tailpipe emissions, or after emissions testing activities have concluded at the monitoring site in a centralized data processing facility. A method for determining the type of fuel of a vehicle is disclosed in U.S. Patent application serial number 09/928,720 entitled "METHOD AND SYSTEM FOR DETERMINING THE TYPE OF FUEL USED TO POWER A VEHICLE", filed August 13, 2001, the disclosure of which is hereby incorporated by reference in its entirety.

[0078] FIG. 9 illustrates a preferred embodiment including a light source 120 capable of emitting at least one beam of light 122 having known emission intensities corresponding to one or more of infrared, visible, and ultraviolet spectra. The system also includes a reflection unit 124, a detection unit 90 capable of receiving the beam and measuring received intensities corresponding to the light spectra, and a processor 92 capable of comparing received intensities and identifying a concentration of a gas of interest. The light 122 is transmitted through a gas, such as air containing vehicle emissions, reflected, then detected for analysis and measurement of the amount of absorption that has occurred at known wavelengths. The amount of absorption may be used to determine concentrations of gases corresponding to the specific wavelengths.

[0079] Preferably, as illustrated in FIG. 10, the system also includes a first reflector 130 positioned to receive the beam 128 from the light source 120 and reflect the beam 132 toward the reflection unit 124. The reflection unit 124 is positioned to receive the beam 132 from the first reflector 130 and reflect the beam 134 toward a second reflector 136. Also preferably, the second reflector 136 is positioned to receive the beam 134 reflected by the reflection unit 124 and reflect the beam 138 toward the detection unit 90. In a preferred

embodiment, each reflector 130,136 comprises an off-axis paraboloidal mirror, however a spherical or other similar mirror could be used.

[0080] Referring to FIG. 11, a paraboloidal mirror 180 has the property that light rays 182 emitted from and diverging from a small spot of a light source 184 placed near the paraboloidal mirror 180 focus 186 are reflected into a beam of rays 188 nearly parallel to the axis of rotation 190 of the mirror.

[0081] Conversely, as illustrated in FIG 12, a beam of light rays 192 traveling nearly parallel to the axis of rotation 190 of a paraboloidal mirror 180 become rays 194 reflected toward and concentrated into a small spot near the paraboloidal mirror focus 186. The significance of a light beam of nearly parallel rays 192 is that the intensity of the light beam changes very little over a great distance, a desirable trait for long path, open-path gas detection systems. Off-axis paraboloidal mirrors have the advantage that the light source or detection unit may be located to the side of the reflected beam instead of in its midst. This means that the full diameter of the mirror can be used for the optical measurements. Layout of the source and detector components is also simplified. Spherical mirrors are more “fuzzy” at the focus, and incoming/outgoing light rays are not nearly as parallel as with the parallel rays 192 of the paraboloidal mirror 180. Light rays that do not travel in the parallel path are lost from the optical path and as a consequence, are part of the reduced efficiency of an optical system that utilizes spherical mirrors. Nonetheless, other factors such as availability of product, production cost, etc. all factor in the decision whether to use the preferred paraboloidal mirror 180 for sending/receiving light in the embodiment, or utilize spherical mirrors in their place.

[0082] Returning to FIG. 10, a beam of light travels along an optical path 128, 132, 134, and 138 from the light source 120, to the first reflector 130, to the reflection unit 124, to the second reflector 136, to the detection unit 90. In this embodiment, the system also includes, as seen in FIG. 13, one or more additional light sources 144,146, each capable of emitting a beam of light 148 ,152 having known emission intensities corresponding to one or more of infrared, visible, and ultraviolet spectra, as well as one or more beam splitter/combiners 140,142, if necessary, positioned to direct beams 148,152 from the additional light sources 144,146 along essentially the same optical path 154, 132, 134, and 138 as illustrated in FIG. 10. The beam splitter/combiners 140,142 may be neutral density filters, or alternatively they may be wavelength sensitive beam splitter/combiners, such as dichroic beam splitter/combiners.

[0083] In another embodiment, illustrated by FIG. 14, the light sources 10,12, beam splitter/combiners 140,160, infrared detector 50, and spectrometer 43 are positioned so that ultraviolet light beam 212 from source 12 is traveling along essentially the same optical path, but in the opposite direction from infrared light beam 14 from source 10. This innovation is referred to herein as "opposed sources". An embodiment using opposed sources may eliminate the need for additional expensive, light attenuating components. For instance, if ultraviolet light 212 is directed towards, instead of away from, the infrared detector 50, the signal from the infrared detector 50 can degrade. If light 212 from an ultraviolet source 12 is traveling in the opposite direction from the light 14 emanating from the infrared source 10, the ultraviolet light 212 is naturally kept away from the infrared detector 50 without the use of additional wavelength dependent filters or beam splitter/combiners. Light sources 12,10 and detectors 43, 50 need to be matched with optical components of corresponding F-numbers for efficient light transmission. An embodiment using opposed sources, and first and

second reflectors 130,136 of significantly different F-number, allows the sources or detectors requiring a higher F-number to be matched with the reflector with the higher F-number, and the sources and detectors requiring a lower F-number to be matched with the reflector with the lower F-number. This eliminates the need for additional optical components for F-number matching. Finally, opposed sources may significantly simplify component layout and reduction of thermal and electrical interference among components.

[0084] FIG. 13 shows one possible arrangement of three sources 120, 144 and 146. In one preferred configuration, the source 120 is an infrared source, the source 144 is a visible light source, and source 146 is an ultraviolet light source. In this example, ultraviolet light reflects off splitter/combiner 142 but does not pass through any splitter/combiners. The infrared light passes through two splitter/combiners. However, the arrangement of these sources may be interchanged in any combination, and one or more source types may be omitted entirely.

[0085] FIG. 14 depicts an ultraviolet source 12 and an infrared source 10. The ultraviolet source 12 could also be combined with a visible light source in a manner similar to the combination shown in FIG. 1, either using a pass through ultraviolet source or by providing an additional splitter/combiner to combine the ultraviolet and visible light.

[0086] Thus, the many features and advantages of the invention are apparent from the detailed specification, and thus, it is intended by the appended claims to cover all such features and advantages of the invention which fall within the true spirit and scope of the invention. Further, since numerous modifications and variations will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation



illustrated and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220